



MG McGrath

GREAT PEOPLE. AMAZING RESULTS.

MG S-SLIP

FLAT LOCK PANEL SYSTEM

DESCRIPTION

The MG S-Slip panel system is sturdy and offers the appearance of a smooth, flat seam with minimal oil canning. It features a slip connection that is mechanically fastened with integrated clips and concealed fasteners. The panels can be radiused or tapered and are installed from the bottom up in a sequential pattern, overlapped, and sealed as required to form a watertight system. The integral gutter channel provides superior drainage and allows for quick fastening without additional parts or assembly making this system easy and high performing

FEATURES AND OPTIONS

- Includes slip connection clips and stiffeners if required
- Panel system to accommodate substructure tolerance of +0 to -1/8 inch
- Panels can be installed over almost any substrate
- Custom alloys available based on material choice
- Stamped shingle options available



MATERIALS & FINISHES

MATERIAL	THICKNESS	SIZES (TYPICAL)	FINISHES
Steel	22 – 26 gauge	Width: 6" to 24" Length: 12" to 114"	MG steel custom patina finishes, or standard and custom colors
Stainless	24 – 26 gauge	Width: 6" to 24" Length: 12" to 114"	Standard and custom colors available
Aluminum	.032" & .040"	Width: 6" to 24" Length: 12" to 114"	Standard and custom colors available
Copper	16oz, 20oz, & 24oz	Width: 6" to 24" Length: 12" to 114"	MG copper custom patina finishes
Zinc	.7mm & .8mm	Width: 6" to 24" Length: 12" to 114"	MG zinc custom patina finishes, or standard and custom colors
Titanium	26 gauge	Width: 6" to 24" Length: 12" to 114"	Standard and custom colors available